





Parameter DM leadin	ng intelligent plastering machine
Plastering Height	320cm (support customization to 500cm
Plastering Width	120cm (can choose 80cm、150cm)
Work Efficiency	4 m2/min
Operating Voltage	220 V 50HZ
Main Motor	Single phase double capacitor motor
Targeting	Microcomputer vertical instrument
Size(length, width height)	110*70*193cm
Weight	About 150kg





Description

Wall plastering master DM series can work with gypsum or mortar spraying machines to realize automatic and rapid smoothing after spraying, reducing the punching before spraying and manual smoothing after spraying. It is an efficient choice for all kinds of gypsum and mortar plastering.

DERUTU Automatic Plastering Machine

- ✓ High quality: the vertical flatness error of the plastered wall is within
- two mm; no hollowing and cracking Fast speed: about 4㎡/min,replace 10 traditional skilled workers
- ✓ Labor saving: no need to recruit and manage a large number of people,
- Saving time: stable electrical appliances, long continuous working time ✓ to ensure efficiency and the construction period
- High output: mechanized construction saves costs, increases profits, and reduces the risk of work-related injuries

Applicable materials and items

- Cement Mortar
- •Self-mixed Mortar
- Anti-cracking Mortar
- ·Lightweight Gypsum
- Polymer Mortar

- •Public Construction projects House Construction Project
- •Office Buildings
- •Industrial Plant
- •Warehouse, etc
- · Heavy Gypsum



Parts List


- ✓ Host
- ✓ Pole (can be customized height)
- ✓ Toolbox

Core Technology

- ①Small and light, can be used in small areas such as internal and external corners, doors, windows and holes
- @Microcomputer automatic leveling system without punching ribs, the error within 2mm ③Siemens PLC + imported servo motor + industrial control LCD screen, automatic control and ad-
- Satellies FLC Thingtones serve motor "muscata control text Screen, automatic control and a justable speed and power supply of the construction site, no need to pull wires to connect to the power supply. The 48V super large battery lasts for more than 10 hours
- ©Electric brake by one-button locking, no need for ceiling fixing, universal for interior and exterior walls, convenient and quick © Patented independent suspension chassis, easy to move on the uneven construction ground
- The plastering scraper device with patented design ,integrates smoothing, filling and scraping
- together ®The host, track, and scraper are snap-connected (patented technology), no screws are needed, so the application efficiency is high
- 9The hoist track is made of 6063 aluminum alloy plate, and the error is guaranteed to be within
- ®Patent lifting safety protection device to prevent accidental machine damage caused by machine lifting







contact: 400-8936-518 Email: info@derutu.com Focus on providing overall solutions for wall construction







