





Parameter [OM technology intelligent plastering machine
Plastering Height	320cm (support customization to 500c
Plastering Width	120cm(can choose 80cm、150cm)
Work Efficiency	4 m2/min
Operating Voltage	48V /storage battery
Main Motor	servo motor
Targeting	Microcomputer vertical instrument
Size(length, width he	ight) 110*70*193cm
Weight	About 175kg





Description

Wall plastering master DM series can work with gypsum or mortar spraying ma-

 $chines \ to \ realize \ automatic \ and \ rapid \ smoothing \ after \ spraying, \ reducing \ the$ punching before spraying and manual smoothing after spraying. It is an efficient choice for all kinds of gypsum and mortar plastering.

DERUTU Automatic Plastering Machine

High quality: the vertical flatness error of the plastered wall is

- ✓ Fast speed: about 4m²/min,replace 10 traditional skilled work-
- ers
 Labor saving: no need to recruit and manage a large number of
- ✓ people, a beginner can start quickly
- ✓ Saving time: stable electrical appliances, long continuous working time to ensure efficiency and the construction period High output: mechanized construction saves costs, increases profits, and reduces the risk of work-related injuries

Applicable materials and items

- Public Construction projects Cement Mortar
- House Construction Project Office Buildings
- Anti-cracking Mortar Industrial Plant
- Lightweight Gypsum Warehouse, etc
- Heavy Gypsum
- Polymer Mortar
- High Ductility Mortar

Parts List

- ✓ Pole (can be customized height)
- ✓ Host ✓ Toolbox

Core Technology

- ①Small and light, can be used in small areas such as internal and external corners, doors, windows and
- ②Microcomputer automatic leveling system without punching ribs, the error within 2mm ③Siemens PLC + imported servo motor + industrial control LCD screen, automatic control and adjustable
- 4 not limited by the voltage and power supply of the construction site, no need to pull wires to connect tothe power supply. The 48V super large battery lasts for more than 10 hours
- ⑤Electric brake by one-button locking, no need for ceiling fixing, universal for interior and exterior walls, convenient and quick
- $\underline{\^{e}}$ Patented independent suspension chassis, easy to move on the uneven construction ground The plastering scraper device with patented design , integrates smoothing, filling and scraping togeth-
- ®The host, track, and scraper are snap-connected (patented technology), no screws are needed, so the
- application efficiency is high

 The hoist track is made of 6063 aluminum alloy plate, and the error is guaranteed to be within 0.05mm
- ®Patent lifting safety protection device to prevent accidental machine damage caused by machine lifting ®Install mobile phone interconnection, remote monitoring machine position, switch time, running time and data collection and storage
- ®sensor failure warning function, wear and tear of consumables can be monitored, maintenance reminders, plastering area, maintenance time and other data can be stored and monitored by chip











